

Parameter	Description	Default	Comments
WSAPPLIANCES	List of appliances	None	Enter the IP or DNS addresses of your WANOP Client Plug-in appliances here, in a comma-separated list in the form of <i>{appliance1, appliance2, appliance3}</i> . If the port used for signaling connections is different from the default (443), specify the port in the form <i>Appliance1: port_number</i> .
DBCMINSIZE	Minimum amount of disk space to use for compression, in megabytes	250	Changing this to a larger value (for example, 2000) improves compression performance but prevents installation if there is not enough disk space. The plug-in will not install unless there is at least 100 MB of free disk space in addition to the value that you specify for DBCMINSIZE.
PRIVATEKEYPEM	Private key for the plug-in. Part of the certificate/key pair used with SSL compression	None	Use Orca's Paste Cell command. The normal Paste function does not preserve the key's format. Should be a private key in PEM format (starting with -----BEGIN RSA PRIVATE KEY-----)
X509CERTPEM	Certificate for the plug-in. Part of the certificate/key pair used with SSL compression	None	Use Orca's Paste Cell command. The normal Paste function does not preserve the key's format. Should be a certificate in PEM format (starting with -----BEGIN CERTIFICATE-----)
CACERTPEM	Certification Authority Certificate for the plug-in. Used with SSL compression	None	Use Orca's Paste Cell command. The normal Paste function does not preserve the key's format. Should be a certificate in PEM format (starting with -----BEGIN CERTIFICATE-----)