


# Configuring Deputy


Configuring Deputy for SSO enables administrators to manage their users using Citrix Gateway. Users can securely log on to Deputy using their enterprise credentials.

To configure Deputy for SSO through SAML, follow the steps below:

1. In a browser, type <https://once.deputy.com> and press **Enter**.
2. On the Login page, type your administrator credentials, and click **Sign In**.



3. On the Profile page, click  icon in the top right corner. Click on your domain name from the drop-down list.



4. Navigate to: [https://\[yourSubDomain\].deputy.com/exec/config/system\\_config](https://[yourSubDomain].deputy.com/exec/config/system_config). The Workplace page appears.



```

1 -----BEGIN CERTIFICATE-----
2 MIIFPzCCBCegAwIBAgIQApjY189Tw/6/mHRS5nGDuzAMBgqhkiG9w0BAQsFADBN
3 NQs=
4 allc
5 HTE
6 BAc
7 LjE
8 ADC
9 yVj
10 Kjf
11 vdE
12 RK2
13 RYC
14 MBa
15 +Cc
16 Y2V
17 BBY
18 LyS
19 Ois
20 MDC
21 dCE
22 GGF
23 Y2V
24 dDA
25 PA6
26 +Xz
27 gSt
28 c+r
29 UOZLmrmupre1cnaJjor3fWlCzckp0u9fWqenWwLAdQ0aLz/m7wz0qBazy4ND
30 6ED5
31 -----END CERTIFICATE-----
32

```

d. Copy the text between -----BEGIN CERTIFICATE----- and -----END CERTIFICATE-----

ii. **Deputy Token to create user on the fly:** In this section, click the [here](#) link.

Deputy Token to create user on the fly

If you want SAML insertion to automatically create a user if they do not exist in Deputy, enter the Deputy access token here which will be used to create the user. Get the access token by creating a client [here](#) and get a token

a. You are navigated to [https://\[yourSubDomain\].deputy.com/exec/devapp/oauth\\_clients](https://[yourSubDomain].deputy.com/exec/devapp/oauth_clients).

New OAuth Client			
Viewing items 1-5 of 5.			
Actions	Name	Client Id	Redirect Uri
	CloudWorks	0b693b36351e0b0dc405d9fd0e454074a41a75b2	https://service-proxy.deputy.com

b. Click **New OAuth Client**.

c. Type the appropriate **Name** and the **Redirect Uri**, and click **Save this OAuth Client**.

d. Click **Get An Access Token**. An Access token appears.

Type this token number in the **Deputy Token to create user on the fly** field.

- iii. **SAML SSO URL:** Enter the IdP URL, SAML 2.0 endpoint, for example, <https://example.com/saml/login>.

- 7. Click **Save Settings**.

The SSO configuration is completed.