Configuring GitHub Enterprise

Users can securely log on to GitHub using their enterprise credentials.

To configure GitHub Enterprise for SSO through SAML, follow the steps below:

- 1. Access your GitHub Enterprise site for example: https://mygithubenterprise.com.
- 2. To log on to your GitHub Enterprise account as an administrator, click **Sign in with a username and password** link.



3. Type user name and password and click **Sign in**.

GitH	GitHub Enterprise				
	Sign in				
Sign in with instead	your username and password of SAML authentication.				
Username					
Password					
	Sign in				
Sign in v	with SAML authentication				

4. On the home page, in the upper right corner, click the Site Admin icon



5. Click **Management console**.



-#*

6. Type the password to access Management console.



7. On the **Settings** page, click **Authentication**.



8. In the Authentication section, specify the following information:



i. Click the autentication type **SAML**.

- ii. To allow authentication of users who do not have access to your identity provider that uses SAML, select the **Allow creation of accounts with built-in authentication (for users not in SAML)** check box.
- iii. If you do not want to demote or promote users based on attributes sent in SAML, select the Disable administrator demotion/promotion. (ignore the administrator attribute) check box.
- iv. **Single sign-on URL** type the IdP URL followed by /saml/login. For example: https://<NetSaclerFQDN>/saml/login
- v. **Issuer** type a unique issuer name.
- vi. Signature Method click RSA-SHA256.
- vii. **Digest Method** click **SHA256**.
- viii. Name Identifier Format click unspecified.
- ix. In the **Verification certificate** area, to upload the IDP signing certificate, click **Choose File**.



Browse to the folder where you saved the IdP provided certificate and upload it. Based on the certificate that you upload, the values for the fields Domain, Alternate names, Issuer, Valid From, and Expires After are automatically populated.

To obtain your IdP certificate, follow the steps below:

- i. Remotely access your NetScaler instance using PuTTY.
- ii. Navigate to /nsconfig/ssl folder (using shell command cd /nsconfig/ssl) and press Enter.
- iii. Type cat <certificate name> and press Enter.

Note: Replace <certificate name> with your IdP signing certificate name.

1	Conception of the second		C. British Print	PROPERTY AND INCOME.		YTI
B	States and a second					ND
2	THE R P. LEWIS CO.		and the second second	and the second second		MD
1	it will be with a magnet					MR
Α	the state of the second st		and the local diversion	successive states of	and share a	aWI
j		S S Course Inc.	a set the second	Street Street Street	A CALL OF A	- Bgl
k i i i i i i i i i i i i i i i i i i i	I THE R. P. LEWIS CO.	A COLUMN TO A	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	and the second s	100 million and	7a1
C	A STREET FOR STREET	the star is put			100 million (1997)	503
a i i i i i i i i i i i i i i i i i i i	Contraction in the last	a stand parts	a de la serie	Comments of the second	- Bernet	FF
+	and and the state		COMPANY OF MARY		States of Street,	H99
V			and the second second	COLUMN TWO IS NOT		hrs

- iv. Copy the text from -----BEGIN CERTIFICATE----- to -----END CERTIFICATE-----.
- v. Paste the text in a text editor and save the file in an appropriate format such as <your IDP signing Certificate>.pem.
- 9. Click Save Settings.



You have completed the required configuration on the service provider which is in this case – GitHub Enterprise.